



Twin-Wall Flexible Covering Panels

With over 25 years experience & built to last

A unique twin-wall, high density polyethylene (HDPE) greenhouse covering combining the best in strength and durability technology at an affordable price.

- Fits all greenhouse styles and types, easily flexes or bends around peaks
- Easy installation, simply overlap and screw in place
- Shatter-proof and weathers wind, hail, snow and ice storms
- Easily cleaned and disinfected - will not grow moss or mildew
- UV inhibitor throughout the material
- Does not yellow or lose light transmission with age
- Shipped economically in rolls or flat panels to save on freight
- 10 year manufacturer warranty
- A great choice for a new construction or existing hoop house or greenhouse
- 3.5 mm XP panels have a 75-80% light transmission value and 2.10 R-value
- 5 mm Pro panels have a 75-80% light transmission value and 2.30 R-value



Easy Installation

- 1) To maximize insulation, attach Solexx on the outside of the frame so it covers all the metal surfaces. (There is no right or wrong side when installing; both sides are UV protected)
- 2) Recommended to buy a width to match your on-center frame spacing - 4', 5' or 6'. See pages 480 for screws/ fasteners
- 3) Overlapping one panel with another, the screws are attached directly through the panel and into the framing. A self-drilling screw with a rubber washer is recommended to attach a screw every 4-6"
- 4) To achieve maximum performance, caulk open ends of the paneling with a 1/4" bead of clear 100% silicone caulking to prevent internal moisture, and maximize R-values

