


Wall Shutters & Propeller Fans



DynaMaster[®]

PROPELLER FANS

- Smart streamlined construction includes back guard (motor side) as standard equipment when ordered without wall housing
- Front guards (propeller side) also available
- Available with galvanized steel wall housing.
- Aluminum propeller, epoxy painted steel orifice
- Totally enclosed motor with ball bearings
- Variable speed with solid state control



Fan Size	Fan Model*	RPM	HP	Certified CFM vs Static Pressure			Cert Max BHP**	Ship Wt
				0	.100	.125		
12"	FQ129	1550	1/9	1380	1280	1245	.105	44
16"	FQ16C6	1160	1/8	2180	2020	1960	.148	56
18"	FN18E4	1760	1/4	3430	3165	3090	.300	124

Fan Side	Wall Housing		Shutter		Inlet Guard		Dimensions	
	Model	Wt	Model	Wt	Model	Wt	A Width	B Height
12"	GS12FQ	15	WAA17	4	GS12	6	16-1/4"	18"
16"	GS16FQ	18	WAA22	8	GS16	8	21-1/4"	23"
18"	GS18FN	22	WAA22	8	GS18	10	23-1/4"	25"

* When used with a 2-speed switch, speed reduction is approximately 30% for low speed. Performances shown are for units without ducts.

** BHP does not include drive losses.

Fan Size	1) Fan Model	Catalog Number	2) Inlet Guard	Catalog Number	Alum Auto Shutter	Catalog Number
12"	FQ129	28-31050	GS12FQ	28-31300	WAA17	28-31070
16"	FQ16C6	28-32010	GS16FQ	28-32300	WAA22	28-32420
18"	FN18E4	28-32400	GS18FN	28-32430	WAA22	28-32420