

Wall Shutters & Propeller Fans



Flo-Master®

Aluminum Wall Shutters

- To keep out wind, rain and back drafts when fan is not in operation
- Precision counterbalanced aluminum blades open easier, wider to permit higher fan capacity
- Nylon bearings throughout are corrosion proof to help prevent sticking
- Corrosion resistant heavy gauge aluminum frame; suitable for dusty or humid applications
- Stainless steel hinge pins will not rust, ensuring easy positive blade action
- All shutter blades are reinforced with polished, galvanized steel rods and equipped with double tie-rods
- Automatic type used with exhaust fans; opens automatically when fan is on, closes automatically when fan is off
- Opens with heavy duty damper motors; spring closed; motor draws only 17 watts
- WAAC models are center pivoted to open easier against static pressures



Specifications:

Fan Size	Wall Housing		Automatic Shutter Aluminum		Inlet Guard		Inside Framed Opening Dimensions		
	Model	Wt	Model	Wt	Model	Wt	A	B	C
12"	WS12FQ	20	WAA1515	4	GS12	4	16-3/4"	18"	24"
16"	WS16FQ	23	WAA2020	8	GS16	4	21-3/4"	23-1/4"	27"
18"	WS18FN	28	WAA2222	8	GS18	5	23-3/4"	25-1/4"	24"
24"	WS24DC	35	WAA2727	7	GS24	5	28-3/4"	30-3/4"	29"
30"	WS30DC	42	WAA3333	10	GS30	7	34-3/4"	36-1/2"	31"
36"	WS36DC	46	WAA3939	15	GS36	10	40-3/4"	42-3/4"	31"
42"	WS42DC	53	WAA4545	18	GS42	12	46-3/4"	49"	33"
48"	WS48DC	78	WAA5454	24	GS48	15	54-3/4"	57-1/4"	39"
54"	WS54DC	106	WAA6060	28	GS54	18	60-3/4"	63-1/2"	40"